

Printing date 27.07.2020

Revision: 19.10.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: ZW PU-FOAM B3 750ML 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Application of the substance / the mixture One component insulation and construction PU foam developed to make a seal between construction parts. · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: Bostik Romania SRL 51 Rasaritului Street (DN7), 070000 Buftea, Ilfov, Romania Phone: +40 (372) 833 300; Fax: +40 (372) 833 301; www.bostik.com; www.denbraven.ro · Further information obtainable from: Product safety department. • 1.4 Emergency telephone number: +40 (372) 833 300 during normal opening times 08:30-17:00 **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 GHS02 flame H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. Aerosol 1 GHS08 health hazard Resp. Sens. 1 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H334 Carc. 2 H351 Suspected of causing cancer. STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure. GHS07 Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 Causes skin irritation. H315 Eye Irrit. 2 H319 Causes serious eye irritation. Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation. H362 May cause harm to breast-fed children. Lact. Aquatic Chronic 4 H413 May cause long lasting harmful effects to aquatic life. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

GB -



Printing date 27.07.2020

Revision: 19.10.2018

# Trade name: ZW PU-FOAM B3 750ML

. Userand asists an	(Contd. of page 1)
<sup>·</sup> Hazard pictogr	ams
GHS02 GHS07	GHS08
· Signal word Da	nger
	ining components of labelling:
	ediisocyanate, isomeres and homologues
· Hazard stateme	
	remely flammable aerosol. Pressurised container: May burst if heated.
	mful if inhaled.
	ses skin irritation.
	ses serious eye irritation.
	v cause allergy or asthma symptoms or breathing difficulties if inhaled.
	v cause an allergic skin reaction.
	pected of causing cancer.
	v cause harm to breast-fed children.
	v cause respiratory irritation.
	y cause damage to organs through prolonged or repeated exposure.
	y cause long lasting harmful effects to aquatic life.
• Precautionary s P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P263	Avoid contact during pregnancy and while nursing.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P33	38 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with local/regional/national/international
1001	regulations.
· Additional info	
	ates. May produce an allergic reaction.
	sive mixtures possible without sufficient ventilation.
	sensitised to disocyanates may develop allergic reactions when using this product.
	g from asthma, eczema or skin problems should avoid contact, including dermal contact, with this
product.	
	ould not be used under conditions of poor ventilation unless a protective mask with an appropriate
	be A1 according to standard EN 14387) is used.
· 2.3 Other hazar	
· Results of PBT	and vPvB assessment

• **PBT:** Not applicable.

(Contd. on page 3)

<sup>–</sup> GB



Revision: 19.10.2018

Printing date 27.07.2020

### Trade name: ZW PU-FOAM B3 750ML

(Contd. of page 2)

• vPvB: Not applicable.

# **SECTION 3: Composition/information on ingredients**

### · 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

<ul> <li>diphenylmethanediisocyanate, isomeres and homologues</li> <li>Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335</li> </ul>	25-50%
alkanes, C14-17, chloro Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Lact., H362	5-25%
propane Flam. Gas 1, H220; Press. Gas (Comp.), H280	2.5-10%
isobutane Flam. Gas 1, H220; Press. Gas (Comp.), H280	2.5-10%
dimethyl ether Flam. Gas 1, H220; Press. Gas (Comp.), H280	2.5-10%
	<ul> <li>Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335</li> <li>alkanes, C14-17, chloro</li> <li>Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Lact., H362</li> <li>propane</li> <li>Flam. Gas 1, H220; Press. Gas (Comp.), H280</li> <li>dimethyl ether</li> </ul>

### **SECTION 4: First aid measures**

### · 4.1 Description of first aid measures

• General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air and to be sure call for a doctor.

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

# **SECTION 5: Firefighting measures**

### · 5.1 Extinguishing media

• Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

(Contd. on page 4)



Revision: 19.10.2018

Printing date 27.07.2020

Trade name: ZW PU-FOAM B3 750ML

(Contd. of page 3)

- 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.

• 5.3 Advice for firefighters

• Protective equipment: Mouth respiratory protective device.

### **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
  Wear protective equipment. Keep unprotected persons away.
  6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.
  Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
  6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
  6.4 Reference to other sections See Section 7 for information on safe handling.
  - See Section 8 for information on personal protection equipment.
  - See Section 13 for disposal information.

# **SECTION 7: Handling and storage**

•7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

- · Information about fire and explosion protection:
- Keep ignition sources away Do not smoke.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- **Requirements to be met by storerooms and receptacles:** Observe official regulations on storing packagings with pressurised containers.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that	t require monitoring at the workplace:

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

WEL Short-term value: 0.07 mg/m<sup>3</sup> Long-term value: 0.02 mg/m<sup>3</sup> Sen; as -NCO

(Contd. on page 5)

GB -



Printing date 27.07.2020

Revision: 19.10.2018

Trade name: ZW PU-FOAM B3 750ML

(Contd. of page 4)

**115-10-6 dimethyl ether**WELShort-term value: 958 mg/m³, 500 ppmLong-term value: 766 mg/m³, 400 ppm

• Additional information: The lists valid during the making were used as basis.

### · 8.2 Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

- Not necessary if room is well-ventilated.
- Short term filter device:
- Filter AX

### · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

Recommended thickness of the material:  $\geq 0.5 \text{ mm}$ 

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection: Safety glasses

• Body protection: Protective work clothing

9.1 Information on basic phys	sical and chemical properties	
General Information		
Appearance:		
Form:	Aerosol	
Colour:	According to product specification	
Odour:	Characteristic	
Odour threshold:	Not determined.	



Printing date 27.07.2020

Revision: 19.10.2018

### Trade name: ZW PU-FOAM B3 750ML

	(Contd. of pag
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	e: Not applicable, as aerosol.
Flash point:	Not applicable, as aerosol.
Flammability (solid, gas):	Not applicable.
· Ignition temperature:	235 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Not determined.
· Explosion limits:	
Lower:	1.7 Vol %
Upper:	18.6 Vol %
· Vapour pressure at 23 °C:	8.3 bar
Density at 23 °C:	0.96 g/cm <sup>3</sup>
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
9.2 Other information	No further relevant information available.

# **SECTION 10: Stability and reactivity**

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity
- Harmful if inhaled.

(Contd. on page 7)

GB



Printing date 27.07.2020

Revision: 19.10.2018

### Trade name: ZW PU-FOAM B3 750ML

	(Contd. of page
· LD/LC50 values relevant for classification:	
ATE (Acute Toxicity Estimates)	
Inhalative LC50/4 h 3-6 mg/l	
115-10-6 dimethyl ether	
Inhalative LC50/4 h 308 mg/l (rat)	
· Primary irritant effect:	
· Skin corrosion/irritation	
Causes skin irritation.	
· Serious eye damage/irritation	
Causes serious eye irritation.	
· Respiratory or skin sensitisation	
May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
May cause an allergic skin reaction.	
· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)	
· Germ cell mutagenicity Based on available data, the classification criteria are not met.	
· Carcinogenicity	
Suspected of causing cancer.	
· Reproductive toxicity	
May cause harm to breast-fed children.	
• STOT-single exposure	
May cause respiratory irritation.	
• STOT-repeated exposure	
May cause damage to organs through prolonged or repeated exposure.	
• Aspiration hazard Based on available data, the classification criteria are not met.	
SECTION 12: Ecological information	
• 12.2 Persistence and degradability No further relevant information available.	
• <b>12.3 Bioaccumulative potential</b> No further relevant information available.	
• <b>12.4 Mobility in soil</b> No further relevant information available.	
· Additional ecological information:	

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

### **SECTION 13: Disposal considerations**

### · 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

<sup>-</sup> GB



Revision: 19.10.2018

Printing date 27.07.2020

Trade name: ZW PU-FOAM B3 750ML

(Contd. of page 7)

· European	· European waste catalogue	
08 05 01*	01* waste isocyanates	
16 05 04*	gases in pressure containers (including halons) containing hazardous substances	
17 06 04	insulation materials other than those mentioned in 17 06 01 and 17 06 03	
HP 3	Flammable	
HP 4	Irritant - skin irritation and eye damage	
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity	
HP 7	Carcinogenic	
HP 13	Sensitising	
HP 14	Ecotoxic	

Uncleaned packaging:
Recommendation: Disposal must be made according to official regulations.

· 14.1 UN-Number · ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name	
ADR	1950 AEROSOLS
IMDG	AEROSOLS (alkanes, C14-17, chloro), MARIN POLLUTANT
• ІАТА	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
· Class	2 5F Gases.
· Label	2.1
·IMDG	
· Class	2.1
Label	2.1
·IATA	
· Class	2.1
Label	2.1



Printing date 27.07.2020

Revision: 19.10.2018

### Trade name: ZW PU-FOAM B3 750ML

	(Contd. of page
14.4 Packing group ADR, IMDG, IATA	not regulated
14.5 Environmental hazards:	
Marine pollutant:	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler):	-
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
Segregation Code	SW22 For AEROSOLS with a maximum capacity of 1 litro Category A. For AEROSOLS with a capacity above 1 litro Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre:
	Segregation as for class 9. Stow "separated from" class except for division 1.4. For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2.
14.7 Transport in bulk according to Anno	ex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

# **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P3a FLAMMABLE AEROSOLS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

• REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

(Contd. on page 10)

<sup>-</sup> GB -



Revision: 19.10.2018

Printing date 27.07.2020

#### Trade name: ZW PU-FOAM B3 750ML

(Contd. of page 9)

#### · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H220 Extremely flammable gas. H280 Contains gas under pressure; may explode if heated. H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H362 May cause harm to breast-fed children.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

#### · Department issuing SDS: Product safety department.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases - Category 1 Aerosol 1: Aerosols – Category 1 Press. Gas (Comp.): Gases under pressure - Compressed gas Acute Tox. 4: Acute toxicity - inhalation - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Resp. Sens. 1: Respiratory sensitisation - Category 1 Skin Sens. 1: Skin sensitisation - Category 1 Carc. 2: Carcinogenicity - Category 2 Lact .: Reproductive toxicity - effects on or via lactation STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4