ZODZ7.E97527 Positioning Devices Certified for Canada

Page Bottom

Positioning Devices Certified for Canada

See General Information for Positioning Devices Certified for Canada



E97527

Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N (lbf)	Operating Temp., °C(°F)		Min. Install. Temp., °C (°F)	Resistant to UV Light	Plenum Rating	Flame Rating
		Min	Max		Min	Max				
NCA 0-46 BL UV	21	5 (0.197)	35 (1.38)	220 (49)	-40 (-40)	85 (185)	0 (32)	Yes	AH-2	V-2
NCA 0-55 BL UV	21	5 (0.197)	47 (1.85)	220 (49)	-40 (-40)	85 (185)	0 (32)	Yes	AH-2	V-2
NCA 0-89 BL UV	21	7 (0.276)	79 (3.11)	220 (49)	-40 (-40)	85 (185)	0 (32)	Yes	AH-2	V-2
NCA 0-100 BL UV	21	7 (0.276)	115 (4.53)	220 (49)	-40 (-40)	85 (185)	0 (32)	Yes	AH-2	V-2
NCA 0-125 BL UV	21	11 (0.433)	117 (4.61)	530 (119)	-40 (-40)	85 (185)	0 (32)	Yes	AH-2	V-2
NCA 0-185 BL UV	21	11 (0.433)	162 (6.38)	800 (180)	-40 (-40)	85 (185)	0 (32)	Yes	AH-2	V-2
NCA 0-246 BL UV	21	12 (0.472)	223 (8.78)	800 (180)	-40 (-40)	85 (185)	0 (32)	Yes	AH-2	V-2
NCA 0-270 BL UV	21	12 (0.472)	253 (9.96)	800 (180)	-40 (-40)	85 (185)	0 (32)	Yes	AH-2	V-2
NCA 0-380 BL UV	21	12 (0.472)	253 (9.96)	800 (180)	-40 (-40)	85 (185)	0 (32)	Yes	AH-2	V-2

Note - All indoor models may be followed by K, indicating 1000 pieces and/ or 1 to 3 alphanumerics indicating color. All UV resistant (outdoor) models may include K suffix, preceding W suffix indicating 1000 pieces.

Last Updated on 2016-11-04

<u>Questions?</u> Print this page <u>Terms of Use</u> <u>Page Top</u>

♦ 2016 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".