

Product fiche concerning the
COMMISSION DELEGATED REGULATIONS

(EU)No 811/2021 of 18 February 2013

(EU)No 811/2021 of 02 August 2013

Models: Outdoor Unit: CWP-M 08 A1 Indoor Unit:None

Air-to-water heat pump Yes

Brine-to-water heat pump No

Low temperature heat pump No

Equipped with a supplementary heater No

Heat Pump Combination Heater No

Parameters shall be declared for Medium-temperature applications

Parameters shall be declared for Average Climate Conditions

Item	Symbol	Value	Unit
Rated Heat Output	Prated	7.621	kW
Seasonal space heating energy efficiency	η_s	138.1	%
Energy Classes		A++	
Seasonal Coefficient of Performance	SCOP	3.53	kWh/kWh
Annual Energy consumption	QHE	4462	kWh
Sound power level indoors/outdoors	LWA	60	dB(A)

Declared capacity for heating for part load at indoor
Temperature 20°C and outdoor temperature Tj

Declared coefficient of performance or primary energy ratio for
part load at indoor temperature 20°C and outdoor temperature Tj

Tj = -7°C	Pdh	6.741	kW	Tj = -7°C	COPd	2.18	
Tj = +2°C	Pdh	4.119	kW	Tj = +2°C	COPd	3.44	
Tj = +7°C	Pdh	2.758	kW	Tj = +7°C	COPd	4.73	
Tj = +12°C	Pdh	2.774	kW	Tj = +12°C	COPd	6.06	
Tj = bivalent temperature	Pdh	6.741	kW	Tj = bivalent temperature	COPd	2.18	
Tj = operation limit temperature	Pdh	6.842	kW	Tj = operation limit temperature	COPd	1.96	
Bivalent temperature	Tbiv	-7	°C	Operation limit temperature	TOL	-10	°C
				Heating water operating limit temperature	WTOL	75	°C
Power consumption in modes other than active mode				Supplementary Heater			
Off Mode	P _{OFF}	0.009	kW	Rate heat output	P _{sup}	-	kW
Thermostat-off mode	P _{TO}	0.009	kW				
Standby mode	P _{SB}	0.009	kW	Type of energy input	-		
Crankcase heater mode	P _{CK}	0.042	kW				

Other items					
Capacity control	Variable		Rated airflow rate, outdoors		- m ³ /h
Outlet temperature capacity control	Variable				
Water flow rate capacity control	Fixed				

Models: Outdoor Unit: CWP-M 08 A1 Indoor Unit:None

Air-to-water heat pump Yes

Brine-to-water heat pump No

Low temperature heat pump No

Equipped with a supplementary heater No

Heat Pump Combination Heater No

Parameters shall be declared for Low-temperature applications

Parameters shall be declared for Average Climate Conditions

Item	Symbol	Value	Unit
Rated Heat Output	Prated	7.580	kW
Seasonal space heating energy efficiency	η_s	189.6	%
Energy Classes		A+++	
Seasonal Coefficient of Performance	SCOP	4.82	kWh/kWh
Annual Energy consumption	QHE	3252	kWh
Sound power level indoors/outdoors	LWA	60	dB(A)

Declared capacity for heating for part load at indoor Temperature 20°C and outdoor temperature Tj

Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20°C and outdoor temperature Tj

Tj = -7°C	Pdh	6.705	kW	Tj = -7°C	COPd	3.11	
Tj = +2°C	Pdh	4.159	kW	Tj = +2°C	COPd	4.70	
Tj = +7°C	Pdh	2.745	kW	Tj = +7°C	COPd	6.31	
Tj = +12°C	Pdh	3.198	kW	Tj = +12°C	COPd	8.20	
Tj = bivalent temperature	Pdh	6.705	kW	Tj = bivalent temperature	COPd	3.11	
Tj = operation limit temperature	Pdh	7.006	kW	Tj = operation limit temperature	COPd	2.77	
Bivalent temperature	Tbiv	-7	°C	Operation limit temperature	TOL	-10	°C
				Heating water operating limit temperature	WTOL	70	°C

Power consumption in modes other than active mode

Supplementary Heater

Off Mode	P _{OFF}	0.009	kW	Rate heat output	P _{sup}	-	kW
Thermostat-off mode	P _{TO}	0.009	kW				
Standby mode	P _{SB}	0.009	kW	Type of energy input	-		
Crankcase heater mode	P _{CK}	0.042	kW				

Other items						
Capacity control	Variable		Rated airflow rate, outdoors		-	m ³ /h
Outlet temperature capacity control	Variable					
Water flow rate capacity control	Fixed					

Contact Details:

CAIROX BELGIUM NV/SA.

Address: Hoogstraat 180, 1930 Zaventem, Belgium