



TECHNICAL DATA

ASB



Article:	ASB (EUROBUTYL®)
Description:	A heavy duty butyl sealant with aluminium foil The bond grows stronger with time.
Thickness:	1mm (ASTM D3652)
Adhesive type:	Modified butyl rubber
Backing:	Aluminium 40µm
Compound Color:	Grey
Release liner :	Siliconised PP 70µm (white)
Initial tack:	Immediately
Bonding:	Maximum after 24hours
Loop tack:	>/= 35N/in ² (ASTM D6195)
Service resistance:	-20°C / +80°C
Fire resistance:	M1
UV resistance	Good (topside of the tape is a pure aluminium foil)

Unless stated otherwise all values given are average. The data above are typical results and subject to change without notice. The tape should be thoroughly tested on the substrates in the particular application they are intended for. The user shall determine the suitability of the product for its intended use and the user assumes all risks and liability whatsoever in connection therewith



Peel adhesion 180° >/= 40N/in (ASTM D3330)

Solids: 100%

Specific weight : >/= 1,3gr/cm³

Shelflife/Storage: The characteristics of the material stay the same for a long time, but for the best use it is recommended to be used in 12 months in originally packed state;
Store in dry, well ventilated room and at max temperature +30°C
Store above 40°C may lead to difficulties to remove release liner