

Information requirements (heat pump space heaters and heat pump combination heaters)							
Model(s): R-AQUA CGW-ID 14 A1 + R-AQUA CGW-OU 14 A1							
Air-to-water heat pump	Y			Low-temperature heat pump	N		
Water-to-water heat pump	N			Equipped with a supplementary heater	Y		
Brine-to-water heat pump	N			Heat pump combination heater	Y		
Parameters declared for	Medium-temperature application						
Parameters declared for	Average climate condition						
Item	symbol	value	unit	Item	symbol	value	unit
Rated heat output (*)	Prated	13	kW	Seasonal space heating energy efficiency	η_s	137	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T_j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T_j			
$T_j = -7$ °C	Pdh	12.0	kW	$T_j = -7$ °C	COPd	2.23	–
Degradation co-efficient (**)	Cdh	1.00	–				
$T_j = 2$ °C	Pdh	7.2	kW	$T_j = 2$ °C	COPd	3.33	–
Degradation co-efficient (**)	Cdh	0.99	–				
$T_j = 7$ °C	Pdh	4.5	kW	$T_j = 7$ °C	COPd	4.72	–
Degradation co-efficient (**)	Cdh	0.97	–				
$T_j = 12$ °C	Pdh	3.1	kW	$T_j = 12$ °C	COPd	5.65	–
Degradation co-efficient (**)	Cdh	0.95	–				
$T_j =$ bivalent temperature	Pdh	12.0	kW	$T_j =$ bivalent temperature	COPd	2.23	–
$T_j =$ operation limit temperature	Pdh	11.8	kW	$T_j =$ operation limit temperature	COPd	2.00	–
For air-to-water heat pumps: $T_j = -15$ °C (if TOL < -20 °C)	Pdh	NA	kW	For air-to-water heat pumps: $T_j = -15$ °C (if TOL < -20 °C)	COPd	NA	–
Bivalent temperature	Tbiv	-7	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval capacity for heating	P _{ych}	NA	kW	Cycling interval efficiency	COP _{ycyc}	NA	–
				Heating water operating limit temperature	WTOL	60	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0.025	kW	Rated heat output (*)	P _{sup}	1.2	kW
Thermostat-off mode	P _{TO}	0.025	kW	Type of energy input	Electric		
Standby mode	P _{SB}	0.025	kW				
Crankcase heater mode	P _{CK}	0.025	kW				
Other items							
Capacity control	variable			For air-to-water heat pumps: Rated air flow rate, outdoors	–	5015	m ³ / h
Sound power level, indoors/outdoors	L _{WA}	47/68	dB	For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	–	NA	m ³ / h
Annual energy consumption	Q _{HE}	8045	kWh				
For heat pump combination heater:							
Declared load profile	L			Water heating energy efficiency	η_{wh}	112	%
Daily electricity consumption	Q _{elec}	4.459	kWh	Daily fuel consumption	Q _{fuel}	NA	kWh
Annual electricity consumption	AEC	915	kWh	Annual fuel consumption	AFC	NA	GJ
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.							

Information requirements (heat pump space heaters and heat pump combination heaters)							
Model(s): R-AQUA CGW-ID 14 A1 + R-AQUA CGW-OU 14 A1							
Air-to-water heat pump	Y			Low-temperature heat pump	N		
Water-to-water heat pump	N			Equipped with a supplementary heater	Y		
Brine-to-water heat pump	N			Heat pump combination heater	Y		
Parameters declared for	Low-temperature application						
Parameters declared for	Average climate condition						
Item	symbol	value	unit	Item	symbol	value	unit
Rated heat output (*)	Prated	12	kW	Seasonal space heating energy efficiency	η_s	183	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T_j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T_j			
$T_j = -7$ °C	Pdh	11.0	kW	$T_j = -7$ °C	COPd	2.79	-
Degradation co-efficient (**)	Cdh	0.99	-				
$T_j = 2$ °C	Pdh	6.2	kW	$T_j = 2$ °C	COPd	4.48	-
Degradation co-efficient (**)	Cdh	0.98	-				
$T_j = 7$ °C	Pdh	4.3	kW	$T_j = 7$ °C	COPd	6.54	-
Degradation co-efficient (**)	Cdh	0.96	-				
$T_j = 12$ °C	Pdh	3.2	kW	$T_j = 12$ °C	COPd	7.24	-
Degradation co-efficient (**)	Cdh	0.94	-				
$T_j =$ bivalent temperature	Pdh	11.0	kW	$T_j =$ bivalent temperature	COPd	2.79	-
$T_j =$ operation limit temperature	Pdh	10.7	kW	$T_j =$ operation limit temperature	COPd	2.74	-
For air-to-water heat pumps: $T_j = -15$ °C (if TOL < -20 °C)	Pdh	NA	kW	For air-to-water heat pumps: $T_j = -15$ °C (if TOL < -20 °C)	COPd	NA	-
Bivalent temperature	Tbiv	-7	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval capacity for heating	P _{ych}	NA	kW	Cycling interval efficiency	COP _{ycyc}	NA	-
				Heating water operating limit temperature	WTOL	60	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0.025	kW	Rated heat output (*)	P _{sup}	1.3	kW
Thermostat-off mode	P _{TO}	0.025	kW	Type of energy input	Electric		
Standby mode	P _{SB}	0.025	kW				
Crankcase heater mode	P _{CK}	0.025	kW				
Other items							
Capacity control	variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	5015	m ³ / h
Sound power level, indoors/outdoors	L _{WA}	47/68	dB	For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	NA	m ³ / h
Annual energy consumption	Q _{HE}	5535	kWh				
For heat pump combination heater:							
Declared load profile	L			Water heating energy efficiency	η_{wh}	112	%
Daily electricity consumption	Q _{elec}	4.459	kWh	Daily fuel consumption	Q _{fuel}	NA	kWh
Annual electricity consumption	AEC	915	kWh	Annual fuel consumption	AFC	NA	GJ
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.							