

**VWR-N
(RAL9016)**

- Swirl diffusers
- Square
- Steel
- White, RAL 9016

Square swirl diffusers with fixed blades type VWR-N (RAL9016)

Square swirl ceiling diffusers with fixed blades

Brand

- Cairox

Application

- For air supply and exhaust in ventilation and air conditioning systems

Material

- Steel

Colour

- Standard colour white, RAL 9016
- Other colours available upon request

Composition

- Fixed blades

Mounting

- Fixing with central screw into the crossbar of the plenum box

Accessories

- Plenum box, type **RER-LB**
- Insulated plenum box, type **RER-LB ISO**
- Regulating valve for plenum box, type **CRC**
- Mounting crossbar for direct duct mounting, type **FGN**
- Mounting crossbar for direct ceiling mounting, type **FHN**

Text for tender

- The square air supply diffusers are of the swirl type with fixed blades. They are made of steel with white powder coating RAL 9016 and supplied with a volume control damper in the plenum box.
- Cairox type **VWR-N+RER-L**

Order example



- **VWR-N, 315 + RER-LB 315 + CRC 250**

Explanation

VWR-N = Diffuser type

315 = Diffuser size (\varnothing diffuser neck connection)

Accessories

RER-LB = Plenum box**CRC** = Regulating valve for plenum box**250** = Plenum box connection diameter

Dimensions				
VWR-N	A [mm]	ØD1 [mm]	#Blades	
125	171	123	8	
160	213	158	10	
200	264	198	12	
250	326	248	14	
315	404	313	16	
355	448	353	17	
400	500	398	18	
500	596	498	20	

		Quick selection																							
VWR-N		125			160			200			250			315			355			400			500		
Q	Ak	0.0099			0.0123			0.0176			0.0226			0.033			0.0359			0.05			0.0618		
	B	1.2	2.4	3.6	1.2	2.4	3.6	1.2	2.4	3.6	1.2	2.4	3.6	1.2	2.4	3.6	1.2	2.4	3.6	1.2	2.4	3.6			
50	Vz	H= 2.7 H= 3.2 H= 3.8	0.08 0.06 0.04	0.05 0.04 0.03																					
	Vk		1.4																						
	X0.25		0.5																						
	Ps		11																						
	Lw(A)		<20																						
100	Vz	H= 2.7 H= 3.2 H= 3.8	0.15 0.11 0.09	0.11 0.09 0.07	0.08 0.06 0.05	0.14 0.1 0.08	0.08 0.06 0.05	0.11 0.09 0.07	0.08 0.07 0.05	0.06 0.05 0.05															
	Vk		2.8			2.3		1.6																	
	X0.25		0.9			0.8		0.7																	
	Ps		45			19		6																	
	Lw(A)		35			26		<20																	
150	Vz	H= 2.7 H= 3.2 H= 3.8	0.23 0.17 0.13	0.16 0.13 0.11	0.13 0.12 0.1	0.21 0.19 0.12	0.15 0.1 0.08	0.11 0.09 0.07	0.1 0.08 0.07	0.08 0.07 0.06															
	Vk		4.2			3.4		2.4		1.8															
	X0.25		1.4			1.2		1		0.9															
	Ps		100			41		14		5															
	Lw(A)		46			38		24		<20															
200	Vz	H= 2.7 H= 3.2 H= 3.8	0.31 0.23 0.18	0.22 0.18 0.14	0.17 0.21 0.16	0.2 0.16 0.13	0.15 0.16 0.11	0.11 0.13 0.11	0.1 0.12 0.1	0.08 0.09 0.07	0.08 0.07 0.06														
	Vk		5.6			4.5		3.2		2.5		1.7		1.5											
	X0.25		1.8			1.6		1.4		1.2		1		1.1											
	Ps		178			72		25		9		3		2											
	Lw(A)		54			46		32		22		<20		<20											
300	Vz	H= 2.7 H= 3.2 H= 3.8																							
	Vk																								
	X0.25																								
	Ps																								
	Lw(A)																								
400	Vz	H= 2.7 H= 3.2 H= 3.8																							
	Vk																								
	X0.25																								
	Ps																								
	Lw(A)																								
500	Vz	H= 2.7 H= 3.2 H= 3.8																							
	Vk																								
	X0.25																								
	Ps																								
	Lw(A)																								
600	Vz	H= 2.7 H= 3.2 H= 3.8																							
	Vk																								
	X0.25																								
	Ps																								
	Lw(A)																								
800	Vz	H= 2.7 H= 3.2 H= 3.8																							
	Vk																								
	X0.25																								
	Ps																								
	Lw(A)																								
1000	Vz	H= 2.7 H= 3.2 H= 3.8																							
	Vk																								
	X0.25																								
	Ps																								
	Lw(A)																								
1200	Vz	H= 2.7 H= 3.2 H= 3.8																							
	Vk																								
	X0.25																								
	Ps																								
	Lw(A)																								


Symbols and specifications

- Q = Air volume in m³/h
- Ak = Effective surface (free area) in m²
- B = Distance between the diffusers in m
- H = Installation height of the diffusers in m
- Vz = Maximum velocity at the occupied zone according to distance between the diffusers and installation height in m/s
- Vk = Average effective velocity through the diffuser in m/s
- X0.25 = Throw length in m at an end velocity Vt of 0,25m/s
- Ps = Static pressure loss given in Pa
- Lw(A) = Acoustic power in dB(A)
- The throw X0.25 is given at an end velocity of 0.25m/s for a smooth ceiling without any obstacles.
- The values are given for isothermal supply air. Throw distances for cooling conditions at -11K can be calculated by dividing the X0.25 values with factor 1.1. For heating purposes at Dt of +11K a multiplier of 1.1 should be applied to the

given $X_{0.25}$ value.

- In order to achieve a high comfort level, selections can be made according to the maximal velocity at the occupied zone V_z . These values are given at distances between diffusers B and installation heights H . Velocities V_z lower than, or equal to 0,25m/s at the occupied zone are advised.
- The pressure losses P_s are given for diffusers without damper or with fully opened damper.
- The acoustic power values $L_w(A)$ are given for diffusers without damper or with fully opened damper without room attenuation. Acoustic powers below 20dB(A) are mentioned as "<20" in the tables.
- For all special requirements, please contact our engineering office.

Placement instruction



RER-LB

- Plenum boxes
- Circular
- Steel



Circular plenum boxes type RER-LB

Circular galvanized steel plenum box **RER-LB** with crossbar. To be combined with (PS/)RWR-N, VWR-N, RWR-2 and PRN

Brand

- Cairox

Application

- Connection of circular ductwork and circular diffusers
- Velocity reduction towards diffusers
- Diffuser mounting on plasterboard or false system ceilings

Material

- Galvanized steel

Composition

- Circular plenum box made out of galvanized steel
- Circular side entry spigot
- Mounted crossbar with M6 screw connection in the middle
- Rubber seal between plenum box and diffuser to make an airtight connection

Accessories

- Circular regulating valve, type **CRC**

Order example

- **RER-LB, 200 + CRC 160**

Explanation

RER-LB = Plenum box type


200 = Size according to diffuser (\varnothing diffuser neck connection)

Accessory

CRC 160 = Volume control damper for plenumbox connection $\varnothing 160$

Other available products

- Insulated plenum box type **RER-LB ISO**



Dimensions					
RER-LB	ØD [mm]	q [mm]	Ød [mm]	b [mm]	h [mm]
100	111	148	80	15	65
125	136	168	100	15	65
160	171	193	125	15	65
200	211	228	160	15	65
250	261	268	200	15	65
315	326	318	250	15	65
355	366	318	250	15	65
400	411	383	315	15	65
500	511	383	315	15	65