



## Concentric pressed reducers with rubber type RDG

Galvanized steel pressed reduction pieces, with rubber sealing.  
Maximum diameter 315 mm.

Connection pieces until  $\varnothing 200$  with airtightness class D to EN 12237, connection pieces bigger than  $\varnothing 200$  with airtightness class C to EN 12237. The airtightness class is also determined by the mounting on the construction site.

### Order example


#### ■ RDG 250/200

Explanation :

**RDG** = Type of reduction

**250** = Largest diameter of reduction

**200** = Smallest diameter of reduction



Dimensions				
ØD [mm]	Ød [mm]	l <sub>1</sub> [mm]	l <sub>2</sub> [mm]	[kg]
100	80	18	40	0.2
125	80	30	40	0.3
125	100	23	40	0.3
150	100	40	40	0.4
150	125	25	40	0.3
160	100	45	40	0.4
160	125	28	40	0.4
160	150	18	40	0.4
180	125	40	40	0.5
180	150	28	40	0.4
180	160	23	40	0.4
200	100	73	40	0.6
200	125	53	40	0.6
200	150	38	40	0.5
200	160	33	40	0.5
200	180	18	40	0.5
250	125	200	40	1
250	150	65	40	0.9
250	160	65	40	0.9
250	180	70	40	0.9
250	200	38	40	0.8
315	150	165	60	1.8
315	160	100	60	1.7
315	180	135	60	1.8
315	200	78	60	1.5
315	250	45	60	1.4

**Dimensions**

For dimensions please check our website [www.cairox.be](http://www.cairox.be)