







C.03

Synthetic duct and fitting

UAE-BD90-K

Ubbink Air Excellent Flexible ducts Bends

Bends 90° type UAE-BD90-K

90° bend including 2 click rings **UAE-CR** and 2 rubber seals **UAE-DR** for use between flexible ducts **UAE-FLEX** in the Air Excellent system

Brand

Ubbink

Application

- Part of the Air Excellent systemAllows short 90° turnsFor mounting in walls, floors and ceilings

Specifications

■ Materiaal: PP

Technical data									
	UAE 62/23	UAE75/34	UAE 90/48	UAE 50x100		UAE 50x140		UAE 60X130/55	
	hor/vert	hor/vert	hor/vert	hor	vert	hor	vert	hor	vert
Q [m³/h]	ΔP [Pa]								
10	1.6	0.5	0.2	1	1	0.1	0.1	1	1
20	4.8	1.9	0.8	1	1.1	0.5	0.4	1	1
30	9.6	4.2	1.9	1	2.5	1.2	0.9	1.1	1
40	16.2	7.5	3.4	1.8	4.4	2.1	1.6	1.9	1.7
50	24.3	11.7	5.2	2.9	6.9	3.2	2.6	3	2.7
60	34.1	16.9	7.6	4.1	9.9	4.6	3.7	4.3	3.9



Synthetic duct and fitting

