



Cold shrinking tapes with aluminium finish type ASB

Heavy duty self-vulcanizing cold shrinking tape with aluminium film and composed of 3 layers

Brand

- SUFIX

Application

- Indoor or outdoor use on all kinds of ductwork to provide an airtight seal, a sure and long lasting moisture-proof barrier against weather influences
- For maximum effect the surface must be clean and free of dust, moisture and other foreign contamination
- Porous or fragile surfaces need pre-treatment
- Storage in a properly ventilated room at a max. temperature of 23°C away from humidity

Material

- Vulcanizing adhesive tape with aluminium film
- 3 layers: viscoelastic butyl adhesive laminated with aluminium film and a paper release liner along the adhesive side
- Fire resistance: M1 classification

Specifications

- Available in 50, 75 or 100 mm width
- Length per roll: 15 m
- Color: silver aluminium
- Thickness: 1 mm
- Temperature resistance: -20°C > +80°C
- Application temperature: +5°C / +35°C
- UV resistant
- Carrier: Aluminium 5/100 mm
- Adhesive type: Butyl rubber

**Text for tender**

- The ductwork connection shall be sealed airtight by means of a self-vulcanizing cold shrinking tape, composed of 3 layers: viscoelastic butyl adhesive laminated with aluminium film and a paper release liner along the adhesive side. Fire resistance M1. Permanent service temperature between -20°C +80°C.
- **Sufix** type **ASB**