



Self-adhesive butyl tape with aluminium finish type ASB PREMIUM

High quality cold applicable tape consisting of a butyl adhesive laminated with an aluminum protective film composed of 3 layers (PET/ALU/PET)

Brand

- SUFIX

Application

- Indoor or outdoor use on all kinds of ductwork to provide an airtight seal, a sure and long lasting moisture-proof barrier against weather influences
- For maximum effect the surface must be clean and free of dust, moisture and other foreign contamination
- The tape should be applied with sufficient pressure to ensure an optimum bonding
- Storage in a well ventilated room at a max. temperature of 30°C away from humidity. Storage above 40°C may lead to difficulties to remove the release liner. Store only in original packed state.

Material

- Carrier: PET/aluminium/PET foil (aluminium colour), thickness 55µm
- Adhesive: Compound of an elastomeric modified butyl rubber (grey colour)
- Protective liner: One-sided siliconized PP 70µm (black/white color)

Specifications

- Available in 50, 75 or 100 mm width
- Length per roll: 15 m
- Color: silver aluminium
- Thickness: 1.0 mm (1.2mm with liner)
- Temperature resistance: -20°C > +80°C
- Application temperature: +5°C / +35°C
- UV resistant
- Reaction to fire: Euroclass E (EN 11925-2 + EN 13501-1)
- Adhesive type: Butyl rubber
- Porous or fragile surfaces need pre-treatment

**Text for tender**

- The ductwork connection shall be sealed airtight by means of a self-vulcanizing cold shrinking tape, composed of 3 layers: viscoelastic butyl adhesive laminated with PET/aluminium/PET film and a paper release liner along the adhesive side. Permanent service temperature between -20°C +80°C.
- Properties:
 - Excellent adhesion
 - Waterproof
 - Good heat stability
 - Good ageing
 - UV resistant
- **Sufix** type **ASB PREMIUM**