



## Aluminium tapes type ALUTAPE FSK

Pure aluminium foil, composed of 3 layers, coated on one face with an acrylic pressures sensitive adhesive, having excellent shear strength particularly at high temperature

### Brand

- SUFIX

### Application

- Used on ductwork to provide an airtight seal, a sure and long lasting moisture-proof and sealing-proof barrier against weather influences
- For maximum effect the surface must be clean and free of dust, moisture and other foreign contamination
- Storage in a properly ventilated room at a temperature between 16 and 27°C

### Material

- Reinforced aluminium foil with an adhesive coat
- 3 layers: aluminium film, UV resistant acrylic adhesive layer and monosiliconised white paper protective liner
- Fire resistance: M1 classification

### Specifications

- Available in 75 mm width
- Length per roll: 50 m
- Colour: silver aluminium
- Thickness: 110 µm
- Temperature resistance: -20°C + 120°C
- Apply temperature: -10°C + 40°C
- Adhesive type: UV-resistant acrylic

### Text for tender

- The ductwork connection shall be sealed airtight by means of UV-resistant pure aluminium foil tape, coated on one face with an acrylic pressures sensitive adhesive. Permanent service temperature between -20°C and +80°C
- **Sufix** type **ALUTAPE FSK**