



## PVC tapes type PVC-TAPE

PVC tape composed of 2 layers

### Brand

- SUFIX

### Application

- Used on ductwork to provide an airtight seal, a sure and long lasting moisture-proof and sealing-proof barrier against weather influences
- Heavy duty outdoor protection, wire and cable harnessing, masking and splicing in ventilation and air conditioning applications
- Slippage prevention for hand-tools and hardware
- For maximum effect the surface must be clean and free of dust, moisture and other foreign contamination
- Storage in a properly ventilated room at a max. temperature of 23°C away from humidity

### Material

- PVC tape with an adhesive coat on one side
- 2 layers: one vinyl and one rubber based pressure sensitive adhesive
- Flame retardant tape, UL listed and CE & CSA certified

### Specifications

- Width of 50 mm
- Length per roll: 33 m
- Colour: grey, white or black
- Thickness: 180 µm
- Temperature resistance: -10°C / +80°C
- Application temperature: +10°C
- Carrier: pure plasticized PVC
- Adhesive type: synthetic rubber based adhesive

**Text for tender**

- The ductwork connection shall be sealed airtight by means of a PVC tape with an adhesive coat on one side, composed of one vinyl and one rubber based pressure sensitive adhesive
- **Sufix** type **PVC-TAPE**.