



Aerosol multi-spray type GT7

GT7 is a multi-spray that can be used in many ways: as penetrating oil, lubricant, fights rust, cleaner and many other applications.

Brand

- TEC7

Specifications

- Packaging: aerosol 400ml
- Boiling point: 187°C – 211°C
- Vapour pressure at 20°C, Pa: 100
- Relative density at 20°C: 0.808
- Physical state at 20°C: liquid
- Flash point: 67°C
- Spontaneous ignition: 255°C
- Water solubility: insoluble
- Dynamic viscosity at 20°C: 1 mPa.s
- Kinematic viscosity at 20°C: 1 mPa.s
- Protective period: 8-12 months, the duration of the protection can be extended by regularly applying GT7. Outdoors this protective period can change, depending on the weather conditions.
- Shelf life: 3 years
- Safety measures: Please consult the safety data sheet

Characteristics

- **MOISTURE REPELLENT**
 - GT7 repels moisture super-fast due to its extremely low surface tension and strong penetrating properties..
- **FIGHTS RUST**
 - GT7 fights rust very quickly by breaking up the rust crystals and through its cold-shrinking effect.
- **PENETRATING OIL**
 - GT7 has a strong penetrating ability, so that it can penetrate into even microscopically small openings.
 - GT7 penetrates under the old grease layer, where it goes to work. GT7 has unblocking properties.
- **LUBRICANT**

- GT7 stops creaks and squeaks in a jiffy. GT7 is an ideal lubricant for fine mechanical and electrical components.
- **CONTACT SPRAY**
 - GT7 detaches oxidation and, thanks to its strong penetrating ability, is the ideal contact spray on electrical installations, home appliances, battery clips, distribution boxes, etc.
- **CLEANER**
 - GT7 cleans pneumatic tools, cylinder locks, deposits of tar, grease, brake fluid, etc.
- **PROTECTIVE AGENT**
 - GT7 fills in all small irregularities and pores and creates a long-lasting, transparent and moisture-repelling layer.