



Fire resistant PU foams type BAP/FP404 PU GUNFOAM

Fire resistant PU foam to be used with Gun type **GUN EASY**

Application

- To cover holes in compartmentation walls
- Can be used in joints from 5 mm to 30 mm wide

Material

- Fire resistant PU foam

Colour

- Pink

Characteristics

- (H)CFK Free
- Density 15/20kg/m³ (ISO7390)
- Building Class B1 (DIN4102-1)
- Temperature resistance -40°C to +90°C
- Head conductivity 0.030 - 0.035 W/mK (DIN52612)
- UV resistance: Weak resistance. To be painted or plastered to protect against UV-rays
- Apply temperature : between +10 and +35°C (ideal between +15 and +20°C)
- Skin formation after 8 to 12 minutes (23°C and 55% RH)
- Cuttable after 20-40 minutes (FEICA TM1005)
- Shelf life: 12 months, when stored dry between +5 and +25°C
- Bottle should always be stored straight up

Certification

- Approved according to EN1366-4 and B1 (DIN 4012-1)

Accessories

- Cleaning wipes, type **CLEANERS**
- PU Gun, type **GUN EASY**

Text for tender

- Openings will be sealed with fire resistant PU foam
- Suffix type **BAP GUNFOAM/FP404 PU Gunfoam**

Order example

- **BAP GUNFOAM/FP404 PU Gunfoam**

Explanation

BAP GUNFOAM/FP404 PU Gunfoam = Fire resistant PU foam for PU-gun