



Contact glue in spray type POWER SPRAY

Contact glue in aerosol spray 500ml

This non-chlorinated glue bonds to most materials including concrete, slate, brickwork, stone, ceramics, wood, metal, rigid plastic, rubber, glass, polythene, canvas, foam, fabrics, cork, cardboard and paper

Application

The adhesive has many uses which include the following:

- Thermal insulation - polyurethane and fibrous insulation, foils foam, cork, ...
- Asbestos removal - fixing polythene sheeting to concrete enclosures prior to removal
- Floor coverings - fixing carpets, carpet tiles, cork tiles, underfelts, ...
- Furniture manufacture - bonding foam to foam and upholstery fabrics
- To glue insulation material (glass wool, rock wool, Sonic,...) on ducts and metal surfaces
- Unsuitable for expanded materials
- Unsuitable for flexible plastics

Composition

- Contains solvent
- 500ml

Order example

- **POWER SPRAY**

Explanation

POWER SPRAY = Type of spray contact glue

Mounting

- The adhesive must be applied on both sides
- With this content of 500ml, you can cover an average area of 2m²
- After 24 hours the adhesive is fully dried
- 5-7 min to dry, then add the two pieces together
- Processing temperature between 18 and 25°C

Accessories

- Cleaning wipes, type **CLEANERS**