

- Insulated ducts PP
- Accessories for ISDR
- Bends



Insulated bend for ISDR ducts type ISDR BD90/45

Insulated bend for mounting of **ISDR** ducts - supplied as a bend of 90°, can easily be reduced to 45°

Order example

ISDR BD90/45 200/170


Explanation:

ISDR BD90/45 = insulated bend

200 = diameter of outer sheath

170 = diameter of inner sheath

Qv [m³/h]	Technical data											
	100	150	200	250	300	350	400	450	500	550	600	
	Ps/m [Pa]											
ISDR BD 90 160/125	0,8	1,7	3,1	5,1	7,1							
ISDR BD 90 200/170			0,9	1,9	2,1	2,8	3,7	4,7	5,9	7,2	8,3	
ISDR BD 90 250/200				0,5	0,8	1,1	1,6	2	2,5	3	3,7	4,5
	Ps/m [Pa]											
ISDR BD 45 160/125	0,4	1,0	1,9	3,0	4,3							
ISDR BD 45 200/170		0,4	0,9	1,7	2,2	2,7	2,2	2,8	3,6	4,3	5,0	
ISDR BD 45 250/200			0,3	0,5	0,7	0,8	1,2	1,6	1,8	2,2	2,5	



	Dimensions		
	D1 [mm]	D2 [mm]	L [mm]
ISDR BD90/45 160/125	125	160	167
ISDR BD90/45 200/170	170	200	201
ISDR BD90 250/200	200	250	215
ISDR BD45 250/200	200	250	215