

**AOYG KRTA SM**

- Fujitsu
- Super Multi
- Outdoor unit
- R32



type AOYG KRTA SM

**Brand**

- Fujitsu

**Refrigerant**

- R32

**Applicable indoor units**

- Type **AUXG 18/22/24 KVLA**
- Type **ARXG 18 KLLAP**
- Type **ARXG 22/24 KMLA**

**Features**

- **Only 3-wire remote controller**
- Robust and compact
- Colour, RAL 7044
- Protected valves
- 3-Bladed rotary fan
- DC twin rotary compressor
- Input power : 400V/3/50Hz
- Permissible range of outdoor temperature in heating: **-15~24°C**

		Combination opportunities			
Gelijktijdige Multi-split		TWIN		TRIPLE	
Aantal binneneenheden		2	2	2	3
Model		AOYG 36 KRTA	AOYG 45 KRTA	AOYG 54 KRTA	AOYG 54 KRTA
Cassettemodellen	Type toestel				
	AUXG 18 KVLA	x			x
	AUXG 22 KVLA		x		
Kanaalmodellen	AUXG 24 KVLA			x	
	ARXG 18 KLLAP	x			x
	ARXG 22 KMLA		x		
	ARXG 24 KMLA			x	

Technische specificaties	Specifications			
		AOYG 36 KRTA	AOYG 45 KRTA	AOYG 54 KRTA
Koelmiddel (GWP)		R32 (675)	R32 (675)	R32 (675)
Maximum luchtdebiet (K/V)	m³/h	3750/3750	4450/4450	4450/4450
Voeding	V	400/3	400/3	400/3
Compressor type		DC Twin Rotary	DC Twin Rotary	DC Twin Rotary
Geluidsdruk (K/V)	dB(A)	55/55	57/57	57/59
Geluidsvermogen (K/V)	dB(A)	70/70	71/71	73/73
Afmetingen (H x B x D)	mm	788x940x320	998x940x320	998x940x320
Gewicht	kg	53	67	67
Koelleidingen	inch	3/8 - 5/8	3/8 - 5/8	3/8 - 5/8
Voorgevulde hoeveelheid koelmiddel	g (CO2eq-T)	1900 (1,28)	2700 (1,82)	2700 (1,82)
Extra hoeveelheid koelmiddel per meter	g/m	40	40	40
Aantal meters voorgevuld	m	30	30	30
Maximum lengte/hoogte koelleiding	m/m	50/30	50/30	50/30
Minimum koelleidinglengte	m	5	5	5
Werkingstemperatuur in koeling	°C	-15~46	-15~46	-15~46
Werkingstemperatuur in verwarming	°C	-15~24	-15~24	-15~24
Sectie voedingskabel	mm²	5G2,5	5G2,5	5G2,5
Automatische zekering (traag)	A	16	16	16

\* Specificaties en design kunnen wijzigen zonder bericht voor verdere verbeteringen  
 \*\* Geluidsvermogen volgens EN12102