



Accessories - Simple wired remote controller type UTY-RSNYM

Brand

- Fujitsu - Airstage

Product

- Single remote controller, wired with Master control button

Application

- For offices with lots of visitors where no detailed functions are needed.
- Controlling of one indoor unit of Multi G range or dual remote controller (slave remote) for indoor unit of Multi G and ASYG Single split range

Applicable indoor units

- Type **ASYG KMCC + UTY-TWBXF**
- Type **AUXG KVLA**
- Type **AUXG KRLB/LRLB**
- Type **ARXG KHTAP/ARYG LHTBP**
- Type **ARXG KSLAP/ARYG LSLAP**
- Type **ARXG KLLAP**
- Type **ARXG KMLA/B**
- Type **AUYG LVLA/LVLB**
- Type **AUYG LRLE/LRLA**
- Type **ARYG LLTA/LLTB**
- Type **ARYG LMLE/LMLA**
- Type **ARYG LHTA**
- Type **ABYG LVTA/B**
- Type **ABYG LRTE/LRTA**
- Type **AGYG LVCA**
- Type **ASYG LMCE + UTY-XCBXZ2**
- Type **ASYG LUCA + UTY-TWBXF2**
- Type **ASYG LTCA + UTY-TWBXF2**
- Type **ASYG LFCA/C**
- Type **ASYG LMTA + UTY-TWRX**

Features

- Compact remote controller provides access to basic functions
- Up to 16 indoor units can be controlled with one remote controller
- Suitable for offices which have many visitors coming in and going out and do not require detailed functions.
- **User-friendly operation**
 - Provides access to basic operation, such as Start/Stop, Fan Control, Master control switching and Temperature setting
 - A large Start/Stop button is provided in the centre of the remote controller

unit for easy operation.

- Can be incorporated with the standard remote controller
- Following an error display, Diagnostics can be carried out on the controller.
- **Simple installation**
 - Can be mounted on the European Mounting Box of 60mm or the JIS built-in box of 83,5mm
- **Background light**
 - Backlight enables easy operation in a darkened room
 - Backlight activates during all button operations, and last 10 seconds in operating mode and 5 seconds in stop mode after a button is pressed.

Dimensions

UTY-RSNYM

