



## Air conditioning and heatpumps

## **UTY-LRJY1**

**Fujitsu** Mono-split Accessories Controllers

# Accessories - I.R. receiver kit type UTY-LRJY1

Necessary to control duct type of serie LUAD, LUAN and LUAK by wireless remote controller

#### **Brand**

Fujitsu Airconditioning

#### **Product**

■ IR receiver unit

#### **Function**

Remote controller, individual type

#### **Applicable indoor units**

- Type ARY 9/12/14/18/22 LUAD
  Type ARY 24/30/36/45 LUAN
  Type ARY 45/54 LUAK

#### **Features**

- Not connectable to ARYA and ARYF
  Standard length of controlling cable between receiver and indoor unit is 5m.
  Maximum length of controlling cable between receiver and indoor unit is 10m. An other connection cable is necessary if length exceeds 5m. See accessories.
  Signal angle of 120° and max. signal distance of 7m
  Dimensions for hole in ceiling or wall: 120 x 60 (H x W) [mm]
  It is required to install the receiver as close as possible against the ceiling if the receiver unit is installed in the wall. Minimum installation height at 2.2m

- receiver unit is installed in the wall. Minimum installation height at 2,2m.

#### **Dimensions**

- Inner part : 122 x 60 x 26,5 (H x W x D) [mm]
- Decoration panel:  $145 \times 90 \times 30 (H \times W \times D)$  [mm]

### **Accessories**

Connection cable with length of 5m. Type WJ029378143005