



Duct models multi Fujitsu type ARXG KMLB MU

Brand

- Fujitsu - Airstage

Product

- Indoor unit split type, duct model

Application

- Cooling or Heating of offices, rooms or shops
- In commercial rooms as embedded in ceiling or hanging from ceiling
- For areas between 60 and 140 m²

Function

- Air-Air Heatpump, inverter type

Refrigerant

- R32

Features

- Obligated horizontal mounting position
- Four fan speeds (High/Medium/Low/QUIET)
- Easy maintenance (two-pieced bottom panel, fan casing dismountable in two pieces)
- Control box integrated in unit casing
- Easy-to-install long-life filters (accessory)
- Slim & compact design
- Interchangeable and removable air inlet, bottom or rear
- Connectable optional electrical heater (connection on printed circuit board)
- Adjustable static pressure up to 150 Pa
- Two-direction drain piping
- Moisture removal
- Automatic adjustable air distribution.
- Auto restart
- Auto-changeover
- ON-/OFF-timer
- Weekly timer
- Setback timer
- Connectable distributing duct
- Connectable fresh air duct (dia. 200 mm)

Applicable outdoor units

- Type **AOYG 30 KBTA4**
- Type **AOYG 36 KBTA5**
- Type **AOEG 30 KBTA4**
- Type **AOEG 36 KBTA5**

Accessories

- Pulsion flange (round, 4xdia.200mm). Type **UTD-RF204**
- Extraction flange (rectangular). Type **UTD-SF045T**
- Air inlet plenum box with 4xdia.200mm. Type **UTD-BF204**
- Air inlet filter box with short side filter access. Type **UTD-LFC25**
- Air inlet filter box with long side filter access. Type **UTD-LFD25**
- Replacement filter for UTD-LFC25 and UTD-LFD25. Type **UTD-LFT25**
- Long-life filter. Type **UTD-LF25NA**

Dimensions

