



Air conditioning and heatpumps

ARXG KMLB MU

- **Fujitsu** Multi-split
- Duct type
- Indoor unit

Duct models multi Fujitsu type **ARXG KMLB MU**

Brand

Fujitsu - Airstage

Product

Indoor unit split type, duct model

Application

- Cooling or Heating of offices, rooms or shops
- In commercial rooms as embedded in ceiling or hanging from ceiling
- For areas between 60 and 140 m²

Air-Air Heatpump, inverter type

Refrigerant

R32

Features

- Obligated horizontal mounting position
 Four fan speeds (High/Medium/Low/QUIET)
 Easy maintenance (two-pieced bottom panel, fan casing dismountable in two
- Control box integrated in unit casing
 Easy-to-install long-life filters (accessory)

- Lasy-to-install long-life inter's (accessory)
 Slim & compact design
 Interchangeable and removable air inlet, bottom or rear
 Connectable optional electrical heater (connection on printed circuit board)
 Adjustable static pressure up to 150 Pa
- Two-direction drain piping
- Moisture removal
- Automatic adjustable air distribution.
- Auto restart
- Auto-changeover
- ON-/OFF-timer
- Weekly timerSetback timer
- Connectable distributing duct
- Connectable fresh air duct (dia. 200 mm)

Applicable outdoor units

- Type AOYG 30 KBTA4

- Type AOYG 36 KBTA5
 Type AOEG 30 KBTA4
 Type AOEG 36 KBTA5





Air conditioning and heatpumps

Accessories

- Pulsion flange (round, 4xdia.200mm). Type UTD-RF204
 Extraction flange (rectangular). Type UTD-SF045T
 Air inlet plenum box with 4xdia.200mm. Type UTD-BF204
 Air inlet filter box with short side filter access. Type UTD-LFC25
 Air inlet filter box with long side filter access. Type UTD-LFD25
 Replacement filter for UTD-LFC25 and UTD-LFD25. Type UTD-LFT25
 Long-life filter. Type UTD-LF25NA

Dimensions

