



J.02

Air conditioning and heatpumps

UTY-RLRY

Fujitsu Mono-split Accessories Controllers

Accessories - Wired controller type **UTY-RLRY**

Brand

Fujitsu - Airstage

Product

Single Remote Controller, Wired

Application

Controlling of one or group of 16 indoor units

Applicable indoor units

- Type ASYG/ASEH KG + UTY-TWRXZ2
 Type ASYG/ASEG KE + UTY-TWRXZ2
 Type ASYG/ASEH KM + UTY-TWRXZ2
- Type ASYG/ASEG 18/24 KM + UTY-TWRXZ2 Type ASYH/ASEH 30/36 KM + UTY-TWRXZ2
- Type ASYG LMTA + UTY-TWRX Type AGYG/AGEG KVCA + UTY-TWRXZ3
- Type ABYG/ABEG KRTA
- Type AUXG KVLA Type AUXG KRLB/LRLB
- Type ARXG KHTAP/ARYG LHTBP
- Type ARXH KMTAP
- Type ARXG KSLAP/ARYG LSLAP
- Type ARXG KLLAP
- Type ARXG KMLA/B Type ARXG KHTB
- Type ARYG 72/90 LHTA
- VRF JIIS/JIII/JIIIL/VIII/VRII/JIVS/JIV/JIVL/VRIV

Features

- Simple operation with built-in weekly / daily timer.
 A single remote controller controls up to 16⁽¹⁾ indoor units.
- Up to 2 wired remote controllers can be connected to a single indoor unit
- Powerful features and compact size
- Incorporates four primary functions into a single unit





- 1. Individual control

- Thermo sensor
 Weekly Timer ⁽²⁾ for summer period
 Setback Timer ⁽³⁾ for winter period

Accurate and comfortable

- Accurately room temperature detection by built-in thermo sensor
- Our system can correspond to various scenes
 High flexibility in sensor location
 Diagnosis check function

- Malfunction diagnosis function
 Eror history (Last 16 error codes can be accessed)
- Simple installation
- Can be mounted on the European Mounting Box of 60MM or the JIS built-in box of 83,5mm

Max.16 indoor units can be controlled by one wired remote controller. In this case every indoor unit gets the same parameter from the controller. Is used f.e. in landscape office.
 Two ON/OFF times can be set for each day of the week

(3) Allows the user to set temperatures for two time spans over the course of each day of the week

Dimensions

120 x 120 x 17 (H x W x D) [mm]