



J.02

Air conditioning and heatpumps

UTY-LNTY

Fujitsu Mono-split Accessories Controllers

Accessories - Wireless remote controller type UTY-LNTY

Brand

Fujitsu - Airstage

Product

Single remote controller, wireless remotre controller

Application

Controlling of one or group of indoor units.

Applicable indoor units

AUXG 07/09/12/14/18/22/24 KVLA

Features

- Start/Stop operation and Start/Stop button
- Operation mode setting and Mode button
- (AUTO,COOL,DRY,FAŇ,HEAT)
- Fan speed setting and Fan button AUTO, HIGH, MED, LOW, QUIET
- Up and down airflow direction and swing button
- Reset button. Carries out a resed.Test run button. This button is used when the air conditioner is installed and cannot be used in normal conditions. Only alloid to activated by autorized service personnel.
- Room temperature setting : AUTO : 18 to 30°C

 - COOL/DRY : 18 to 30°C
- HEAT : 16 to 30°C
 Built-in daily timer
 - <u>PROGRAM timer</u>: Operates the ON and OFF timer once within a 24 hour <u>SLEEP & NICE MORNING TIMER (Sleep button) :</u>
 <u>SLEEP : This nocturnal disconnection program adjusts the microprocessor</u>
 - - to the time of year to condtion the room in an optimum manner before the user wakes up.
 - NICE MORNING TIMER (NMT): This function calculats the time required for



Air conditioning and heatpumps

- the room to reach the desired temperature at the time set, and turns on the unit when required.
 <u>ON timer</u>: Switch ON the unit according to the time setting (From 1 to 24 hours Daily)
 <u>OFF timer</u>: Switch OFF the unit according to the time setting (From 1 to 24 hours Daily)
 Easy installation and operation
 Code selector switch prevents indoor unit mix-up (Up to 4 code can be set)
 Wide (120°) and precise transmitting range (max. 7m)
 Batteries and remote control unit holder included
 Specifications : 1,5V (R03/LR03/AAA) x 2

Dimensions

145 x 90 x 30 (H x B x D) [mm]