





J.02

AKD

CAIROX - Daitsu Monoblock Air/air R32



Monoblock air conditioners type AKD

The Cairox - Daitsu window unit is a monoblock window air conditioner. These window air conditioners can regulate the temperature and dehumidify the room, increasing the comfort of the room, studio or home.

In the summertime, the unit can cool the environment and in the wintertime, all with a simple and quick installation.

The device is standard equipped with a built-in controller as well as an infrared

remote control.

Brand

Daitsu

Application

- Apartment buildings
- Container rooms
- Offices
- Hotel and catering, when the installation of an outdoor unit is not possible

Compostion

- Monoblock window model
- Built-in regulationIR controller

Refrigerant

■ R32

Specifications			
Technical specifications		WINDOW 09	WINDOW 12
Cooling capacity	kW	2.7	3.65
Dehumidification	L/h	1.0	1.6
SEER		5.2	5.4
Absorbed power	kW	0.782	1.03
Absorbed current	Α	3.5	4.6
Power supply	V	230/1	230/1
Air flow rate inside (min - max)	m³/h	320 - 400	380 - 480
Air flow rate outside	m³/h	1.359	2.039
Sound pressure level (inside/outside)	dB(A)	50/46	
Compressor type		Rotary DC inverter	
Refrigerant (GWP)		R32 (675)	
Amount of refrigerant	kg	0.51	0.63
Dimensions (H x W x D)	mm	375 x 560 x 708	420 x 660 x 700
Weight	kg	43	50
Operating temperature in cooling mode	°C	+16 ~ +43	