



Compact steam humidifiers type LMV

Compact electrode humidifier with a simple ON/OFF control and a steam flow rate of 2 to 4 kg/h. Suitable for tap water.

Brand

- Vapac

Application

- Office buildings
- Hospitals
- Pharmaceutical industry
- Computer rooms
- Printing industry
- Warehouses
- Museums

Material

- Housing made of pre-lacquered sheet steel
- Plastic steam cylinder

Specifications

- Suitable for external ON/OFF control
- Easy access via inspection door
- Equipped with LED for operating status indication
- Delivery of an **LMV** steam humidifier includes:
 - Steam nozzle
 - Steam hose 1,5m Ø22
 - Condensate hose
 - Flexible hose for water supply with 3/4" connection

Accessoires

- S team hose, type **ST-HS 22/31**
- Automatic room hygostat, type **HR-S/ EBERLE 6001** for ON/OFF control
- High limit safety hygostat for duct mounting, type **HMH** for ON/OFF control
- Safety pressostat, type **DTV**
- Steam blower, type **RDU**

Order example

LMV 422

LMV = Type of humidifier

4 = Steam capacity in kg/h

2 = Number of electrodes

2 = Heating voltage 230V AC

Technical data		222	422
Steam capacity	kg/h	2	4
Rated power	kW	1.53	3.07
Phase	number	1	1
Voltage	V	230	230
Current	A	7	14
Power cable section	mm ²	3G 1,5	3G 1,5
Device data			
Steam cylinder	piece	1	1
Dimensions	width mm	325	325
	height mm	500	500
	depth mm	235	235
Weight (empty)	kg	16	16
Operating weight (max.)	kg	34	34
Steam diffuser			
DUSE	piece	1	1
Steam blower			
4 kg/h	piece	1	1
Steam hoses			
Steam hose Ø 22/31 mm	meter	1	1