

## ED TOUCH

- Controllers
- for units type GTDHR/V, HEXAMOTION (-S), FREETIME (-S), SILVERTOP, NEOTIME, EVERSKY



## Digital controller type ED TOUCH

Touch display for remote control

**Appropriate for units type GTDHR/V , Hexamotion , Freetime, Silvertop, Neotime and Eversky**

**Cable:** 4 cables 24V DC (C+/G0). Cable 10m included.

### Application

Programming and reading-out of the regulator  
Appropriate for GTDHR/V, Hexamotion(-S), Freetime(-S), Silvertop, Neotime and Eversky units or for corrigo regulators

### Specifications

- Reading and setting of set point (+3/-3°C)
- Reading and setting of either room, extraction or outside air temperature depending on the programming of the Corrigo on the unit
- Reading of all issued alarm signals of the Corrigo regulator
- Easy setting of overtime (1, 2 or 3 hours)
- Setting clock/timers

Technical data	
Product Specifications	
Safety class	IP30
Power supply	24 V DC via terminal 4 (+C) and G0 on Corrigo
Power consumption	50mA
Connection cable	Twisted pair, 0,25mm <sup>2</sup>
Display	TFT-LCD (resistive), backlit LED
Language	Swedish or English, automatic setting according to language used in Corrigo
Aspect ratio	4:3
Resolution	320x240
Dimensions (HxLxD)	90 x 120 x 27 mm
Mounting	Room or device box
Communication	EXOnline